



Key Features

- New design slim type flood light
- Epistar COB as light source, high CRI above 70Ra, 90 lumen per watt
- Aluminum housing, good heat dissipation
- 10W-200W version, according to the driver, 3-5 years warranty will be offered
- 120 degree beam angle
- CE RoHS passed
- IP65 protection level

Image Show



Application



Scene lighting; Security lighting; Parking garage lighting; Banner/ flagpoles lighting; Modern and business outdoor lighting; Building lighting for shelters, halls, passages, windows; Decorative lighting for holiday, trade-shows, exhibitions

Specification

SKU	WQF-FG10W07	WQF-FG20W07	WQF-FG30W07	WQF-FG50W07	WQF-FG100W07	WQF-FG150W07	WQF-FG200W07
Power	10W	20W	30W	50W	100W	150W	200W
Lumen	900 lm	1800 lm	2700 lm	4500 lm	9000 lm	13500 lm	18000 lm
PF	>0.5	>0.9	>0.9	>0.9	>0.9	>0.9	>0.9
Input Voltage	85-265 VAC						
CCT	3000K, 4000K, 5000K, 6000K						
CRI	Ra>70						
Efficiency	90 lm/w						
LED Chip	Epistar COB						
LED Driver	CE passed driver, Mean Well Driver						
Housing Color	Black						
IP Grade	IP65						
Beam Angel	60°, 120°						
Material	Aluminum						
Working Temp.	-30°C ~ +45°C						
Lifespan	50000 hours						
Warranty	3-5 year						

Packing Information

SKU	Power	PCS/CTN	KG/PCS	Gross Weight	CBM
WQF-FG10W07	10W	20	0.5 KG	10.50 KG	27*26*33 cm ≈0.023 m ³
WQF-FG20W07	20W	10	1.1 kg	12.00 KG	34*32*23 cm ≈0.025 m ³
WQF-FG30W07	30W	8	1.7 KG	13.80 KG	42*26*27 cm ≈0.029 m ³
WQF-FG50W07	50W	5	2.5 KG	13.00 KG	37*26*33 cm ≈0.031 m ³
WQF-FG100W07	100W	2	4.7 KG	9.5 kg	40*32*21 cm ≈0.029 m ³
WQF-FG150W07	150W	2	5.7 KG	12 KG	47*35*30 cm ≈0.049 m ³
WQF-FG200W07	200W	2	6.25 kg	13 KG	47*35*30 cm ≈0.049 m ³